

3-APH-GS-F-C-C – Cast Air Pipe Head 3?

SKU: 3-APH-GS-F-C-C



Description

- Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

Specification Table

_approximate_weight_lb	'50
closing_device_option	Closing Device
connection	Flanged
construction	Internal housing is removable for easy maintenance
dimension_c_in	'8.5
dimension_d_in	'10.5
dimension_e_in	'10.38
dimension_f_in	'6.25
dimension_g_in	'4.25
flame_insect_screen	Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance
float_option	Stainless Steel (Standard)
flow_rate_at_3_625_psi_gpm	'315

hardware	Stainless Steel
material	Galvanized Steel
max_inlet_air_speed_mpers	'27
minimum_order	1
nitrile_seal	Maximize Low Pressure Sealing Oil And Fuel Resistant
package_type	Each
units_per_package	1
notes	Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

HYDRASEARCH