

70RMODEL4 – AQ-22 Rudders

SKU: 70RMODEL4



Description

- To select the correct AQ-22 Rudder, an estimate of the maximum operating speed and displacement of the boat must be determined. If the displacement cannot be determined, boat length parameters for selecting the appropriate rudder are available in attached charts. The speed at which a boat is typically driven will impact the choice of rudder size. Generally, the heavier and slower the boat, the larger the rudder required. Although these rudders have been designed to handle 40 knots, selecting a rudder which is too large will restrict the boat from achieving full speed, and one too small will lead to steering difficulties. In selecting the length of the rudder stock, consideration must be given to mounting the steering system quadrant or arm at the correct height, leaving some room for the installation of emergency steering equipment. If a specific length is required, it must be stated when ordering the rudder. Otherwise, the length noted in the catalog will be supplied. The charts attached have been formulated to assist in making the appropriate selection for one, two, or three rudder options. In the event the requirements of a particular boat are outside the parameters of the stock design AQ-22 Rudders, please contact the manufacturer for more information. *Stock length (L) to be determined by customer. Roman numerals indicate recommended rudder model; dashed lines indicate approximate boat length. Rudder torque has been increased 25% to allow for bearing friction. Rudder torque is included so that the force required at the tiller arm may be estimated. Stock length (L) to be determined by customer. * Rudder torque has been increased 25% to allow for bearing friction.

Specification Table

dimension_c_in	23.38"
dimension_d_in	11.63"
dimension_e_in	17"
package_type	Each

units_per_package	1
-------------------	---

HYDRASEARCH