

## 5-APH-GS-F – Fabricated Air Pipe Head 5?

SKU: 5-APH-GS-F



### Description

- Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

### Specification Table

|                            |                                                                               |
|----------------------------|-------------------------------------------------------------------------------|
| _approximate_weight_lb     | '83                                                                           |
| closing_device_option      | None (Standard)                                                               |
| connection                 | Flanged                                                                       |
| construction               | Internal housing is removable for easy maintenance                            |
| dimension_c_in             | '11                                                                           |
| dimension_d_in             | '11.5                                                                         |
| dimension_e_in             | '13.38                                                                        |
| dimension_f_in             | '7.17                                                                         |
| dimension_g_in             | '5                                                                            |
| flame_insect_screen        | Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance |
| float_option               | Stainless Steel (Standard)                                                    |
| flow_rate_at_3_625_psi_gpm | '540                                                                          |

|                                  |                                                                                                                                  |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>hardware</b>                  | Stainless Steel                                                                                                                  |
| <b>material</b>                  | Galvanized Steel                                                                                                                 |
| <b>max_inlet_air_speed_mpers</b> | '19                                                                                                                              |
| <b>minimum_order</b>             | 1                                                                                                                                |
| <b>nitrile_seal</b>              | Maximize Low Pressure Sealing Oil And Fuel Resistant                                                                             |
| <b>package_type</b>              | Each                                                                                                                             |
| <b>units_per_package</b>         | 1                                                                                                                                |
| <b>notes</b>                     | Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate. |

HYDRASEARCH