

8-APH-SS-S-P-C – Fabricated Air Pipe Head 8?

SKU: 8-APH-SS-S-P-C



Description

- Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

Specification Table

| | |
|----------------------------|---|
| _approximate_weight_lb | '196 |
| closing_device_option | Closing Device |
| connection | Socket Weld |
| construction | Internal housing is removable for easy maintenance |
| dimension_c_in | '16.5 |
| dimension_d_in | '17.5 |
| dimension_e_in | '20 |
| dimension_f_in | '10.8 |
| dimension_g_in | '6.75 |
| flame_insect_screen | Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance |
| float_option | Polyethylene (Hdpe) |
| flow_rate_at_3_625_psi_gpm | '1410 |

| | |
|----------------------------------|--|
| hardware | Stainless Steel |
| material | Stainless Steel 316 |
| max_inlet_air_speed_mpers | '27 |
| minimum_order | 1 |
| nitrile_seal | Maximize Low Pressure Sealing Oil And Fuel Resistant |
| package_type | Each |
| units_per_package | 1 |
| notes | Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate. |

HYDRASEARCH