

## 2-APH-SS-S-C-P – Cast Air Pipe Head 2?

SKU: 2-APH-SS-S-C-P



### Description

- Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

### Specification Table

|                            |                                                                               |
|----------------------------|-------------------------------------------------------------------------------|
| _approximate_weight_lb     | 24"                                                                           |
| closing_device_option      | None (Standard)                                                               |
| connection                 | Socket Weld                                                                   |
| construction               | Internal housing is removable for easy maintenance                            |
| dimension_c_in             | 6"                                                                            |
| dimension_d_in             | 7.5"                                                                          |
| dimension_e_in             | 7.5"                                                                          |
| dimension_f_in             | 4.5"                                                                          |
| dimension_g_in             | 3"                                                                            |
| flame_insect_screen        | Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance |
| float_option               | Polyethylene (Hdpe)                                                           |
| flow_rate_at_3_625_psi_gpm | 150"                                                                          |

|                                  |                                                                                                                                  |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>hardware</b>                  | Stainless Steel                                                                                                                  |
| <b>material</b>                  | Stainless Steel 316                                                                                                              |
| <b>max_inlet_air_speed_mpers</b> | 36"                                                                                                                              |
| <b>minimum_order</b>             | 1                                                                                                                                |
| <b>nitrile_seal</b>              | Maximize Low Pressure Sealing Oil And Fuel Resistant                                                                             |
| <b>package_type</b>              | Each                                                                                                                             |
| <b>units_per_package</b>         | 1                                                                                                                                |
| <b>notes</b>                     | Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate. |

HYDRASEARCH