

## 2.5-APH-GS-S-C-P – Cast Air Pipe Head 2.5?

SKU: 2.5-APH-GS-S-C-P



### Description

- Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

### Specification Table

_approximate_weight_lb	26"
closing_device_option	None (Standard)
connection	Socket Weld
construction	Internal housing is removable for easy maintenance
dimension_c_in	6"
dimension_d_in	7.5"
dimension_e_in	7.5"
dimension_f_in	4.5"
dimension_g_in	3.5"
flame_insect_screen	Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance
float_option	Polyethylene (Hdpe)
flow_rate_at_3_625_psi_gpm	160"

<b>hardware</b>	Stainless Steel
<b>material</b>	Galvanized Steel
<b>max_inlet_air_speed_mpers</b>	22"
<b>minimum_order</b>	1
<b>nitrile_seal</b>	Maximize Low Pressure Sealing Oil And Fuel Resistant
<b>package_type</b>	Each
<b>units_per_package</b>	1
<b>notes</b>	Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

HYDRASEARCH