

## 6-PM1-A-F-P-C – Inverted Vent Check (Half Float) 6?

SKU: 6-PM1-A-F-P-C



### Description

- Prevents seawater from entering tanks <br> Allows air/vapor to escape when tank is filling<br> Allows air intake when tank is discharging<br> Inverted (gooseneck) design offers simplest means for your requirements<br> Design makes disassembly fast and easy

### Specification Table

_approximate_weight_lb	52"
closing_device_option	Closing Device Innovative design is simple and cost effective
connection	Flanged
construction	Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points
dimension_c_in	11.13"
dimension_d_in	9"
dimension_e_in	11"
dimension_f_in	3.5"
dimension_g_in	1"
flame_insect_screen	Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance
float_option	Polyethylene

<b>flow_rate_at_3_625_psi_gpm</b>	890"
<b>hardware</b>	Stainless Steel
<b>material</b>	Aluminum 535
<b>max_inlet_air_speed_mpers</b>	9"
<b>minimum_order</b>	1
<b>nitrile_seal</b>	Maximize Low Pressure Sealing Oil And Fuel Resistant
<b>package_type</b>	Each
<b>pipe_size_a_in</b>	6 In"
<b>units_per_package</b>	1
<b>valve_cap</b>	Eliminates need for a spacer ring and protective screen
<b>notes</b>	Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.